

## Specification Sheet

### CF9 – Magnetic Flexible Rubber Sheet

**Product:**

Steel Paper

**Structure:**

Coated Paper  
LDPE  
Iron Coating  
LDPE  
Coated Paper

Thickness of Iron	25 micron	
Thickness of Paper	67 micron (each side)	
Weight of Paper	79.1g/m <sup>2</sup>	
Thickness of LDPE	30 micron (each side)	
Total Thickness	0.22mm +/-0.01mm	
Specific Gravity	Iron Foil	7.81
	LDPE	0.92-0.93
	Coated Paper	0.83-0.86

**Storage Stability and Handling:**

Care should be taken to avoid direct contact with the sharp edges.  
Corners of the steel paper should be rounded with a radius is not protected.  
Special precautions for transport and storage: Avoid high temperature and humidity.  
Avoid wetting.  
Hazardous decomposition product: Iron foil might get rusty by absorption of excessive moisture on edges.  
Waste Disposal: Burn and Bury

**Fire and Explosion:**

Flash point	Not applicable
Extinguishing Media	Water, chemical for fire extinguishing purposes
Special fire and explosion hazard	Not applicable

**Toxicological Data:**

Not applicable

**Health Hazard:**

Not applicable

The information and data contained herein is believed to be accurate and reliable. However it is the user's responsibility to determine suitability for use. C B Frost & Co makes no warranties concerning fitness or suitability of its products for a particular use or purpose. C B Frost & Co reserve the right to alter the material specification at any time, without prior notice.